

Bona DC Polish™

Technical data sheet

A durable, urethane acrylic blend with an exceptionally fast dry time and no waxy build-up. Adds a high gloss or low gloss protective layer and fills in microscratches, evening out the appearance of the floor.

- Excellent flow and leveling
- Available in high gloss & low gloss
- GREENGUARD Indoor Air Quality Certified®
- Fast drying – approximately 1 hour
- No limited pot life and no wasted finish
- Nonflammable and virtually odorless
- Water clean-up

Technical data

Physical Characteristics:

Ingredients – Water, polymers, diethylene glycol monoethyl ether, and surfactants

Color – Milky white (wet)

pH – 8.0-9.0

Solids – 10% - High Gloss. 13% - Low Gloss

Density – 8.39 lbs./gallon (1.01 S.G.)

US Regulatory VOC – <1%

Gloss Level (60°) >80 for High Gloss, 30-40 Low Gloss

Odor – Non-offending

Stability – 1 year shelf life in unopened container

Packaging – 1-gallon plastic bottle

Application Characteristics:

Clarity – Clear when dry

Leveling – Excellent

Defoaming - Excellent

Drying Time – 1 hour

Coverage – 2,000 square feet per gallon

Percent Cured After 24 Hours – 90%

Maximum Cure – 100% after 72 hours

Recommended Use

- Residential- kitchens, entryways, family rooms, homes with pets, children and high foot traffic as a maintenance coating.
- Use every 1-3 months depending on foot traffic.

Directions

BEFORE USING, READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEETS.

FOR TECHNICAL ADVICE: Call Bona US at 800/872-5515

RECOMMENDED APPLICATORS: Bona Microfiber Applicator Pad

MIXING INSTRUCTIONS: Gently rock bottle back and forth for 30 seconds.

APPLICATION DIRECTIONS:

1. Remove all furniture, rugs, etc. from floor to be treated.
2. Dry sweep the entire floor using Bona's microfiber dusting pad to remove any loose dirt and debris.
3. Deep clean entire floor using the Bona Deep Clean System™. For most wood floors one or two cleaning passes with the Bona PowerScrubber™ filled with Bona Deep Clean Solution™ will thoroughly clean the floor. For heavily soiled areas more passes may be needed to remove ground in dirt. Upon completion of deep cleaning, damp tack(using water only) entire floor to remove any excess cleaning solution missed by the autoscrubber.
4. Pour a 2"-3" wide line of polish going across the grain of the wood floor. Work in small sections to avoid polish drying on the floor prior to being smoothed out.
5. Using the Bona Microfiber Applicator Pad, spread/pull the polish across the floor. Once spread, smooth the polish out by pulling and pushing the applicator with the grain. When

Coatings



Bona®

Bona DC Polish™

Technical data sheet



lowering or lifting the applicator pad from the floor, do so in a gradual and gentle manner, avoiding hard stops and starts. In most cases, the applicator pad will allow application in corners and under toe kicks. If you cannot reach a portion of the floor, use a cut in pad or foam brush to apply. Continue to work the floor in sections till entire floor is coated.

6. Be sure you are applying the polish at 2000 square feet per gallon.

For Best Results: Always test in an inconspicuous section of the floor before use. Coverage should be 2000 square feet per bottle. Do not apply the product too thin or streaking can occur. Coat the entire floor to ensure an even appearance.

Precautions: Do not use over any floor that has been waxed, oiled or polished. Wax, oil and polish will prevent Bona DC Polish from adhering. Only use a clean Bona Microfiber Applicator pad to apply Bona DC Polish. Use of contaminated applicator pads or string, cotton, or sponge mops will cause a cloudy white appearance. Do not mix with any other products.

DRY TIMES: Allow floor to dry for 1 hour before light foot traffic. Allow 24 hours before gently replacing furniture and normal foot traffic.

Maintenance

CURE TIME: 70% cured after 2 hours (light foot traffic), 90% cured after 24 hours (normal foot traffic, furniture may be gently replaced), 100% fully cured after 72 hours. Do not replace carpets or area rugs, clean floor, or expose to heavy traffic for one week.

CLEAN-UP: Application tools should be cleaned with water and stored in an airtight container

STABILITY: One year shelf life in unopened container

STORAGE: Nonflammable – Bona DC Polish should be stored in a climate controlled environment. Keep from freezing. Do not store above 100F.

Order Information

Item #	Size	#/Case
WP510018002	1 Ga. - High Gloss	2
WP500318002	1 Ga. - Low Gloss	2